

60V N-Channel Enhancement Mode MOSFET

Description

The PECN6020SR uses Shield Gate Trench technology that is uniquely optimized to provide the most efficient high frequency switching performance.

Both conduction and switching power losses are minimized due to an extremely low combination of $R_{DS(ON)}$ and Q_g . This device is ideal for high-frequency switching and synchronous rectification.

General Features

- ◆ $V_{DS} = 60V$ $I_D = 20A$
 $R_{DS(ON)}(Typ.) = 2.8m\Omega$ @ $V_{GS} = 10V$
 $R_{DS(ON)}(Typ.) = 4.1m\Omega$ @ $V_{GS} = 4.5V$
- ◆ Excellent gate charge x $R_{DS(on)}$ product(FOM)
- ◆ Very low on-resistance $R_{DS(on)}$
- ◆ 150 °C operating temperature
- ◆ 100% UIS tested


100% UIS TESTED!

Application

100% ΔV_{ds} TESTED!


- ◆ Synchronous Rectification in DC/DC and AC/DC Converters
- ◆ Industrial and Motor Drive applications

Schematic diagram



Marking and pin assignment

SOP-8



XXXX—Date Code
YYYY—Quality Code.



Ordering Information

Part Number	Storage Temperature	Package	Devices Per Reel
PECN6020SR	-55°C to +150°C	SOP-8	4000

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

parameter		symbol	limit	unit
Drain-source voltage		V_{DS}	60	V
Gate-source voltage		V_{GS}	±20	V
Continuous Drain Current	TC=25°C	I_D	20	A
	TC=70°C		16	
Pulsed Drain Current		I_{DP}	80	A
Avalanche energy($T_j=25^\circ C$, $V_{DD}=30V$, $V_G=10V$, $L=0.5mH$, $R_g=25\Omega$)		E_{AS}	320	mJ
Power Dissipation	TC=25°C	P_D	3	W
	TC=70°C		2.1	
Operating junction Temperature range		T_j	-55—150	°C

Electrical Characteristics (TA=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	60	-	-	V
Zero gate voltage drain current	I _{DSS}	V _{DS} =60V, V _{GS} =0V	-	-	1	μA
		T _J =85°C	-	-	5	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V	-	-	±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1.0	1.48	2.0	V
Drain-source on-state resistance	R _{DS(ON)}	V _{GS} =10V, I _D =20A	-	2.8	4	mΩ
		V _{GS} =4.5V, I _D =12A		4.1	6	
Forward Transconductance	g _{FS}	V _{DS} =5V,I _D =20A	35	-	-	S
Diode Characteristics						
Diode Forward Voltage	V _{SD}	I _{SD} =10A,V _{GS} =0V	-	0.82	1.2	V
Diode Continuous Forward Current	I _S		-	-	16	A
Reverse Recovery Time	t _{rr}	T _J = 25°C, I _F = I _S di/dt = 100A/μs	-	40	-	ns
Reverse Recovery Charge	Q _{rr}		-	50	-	nC
Dynamic Characteristics						
Gate Resistance	R _G	V _{GS} =0V, V _{DS} =0V,f=1MHz	-	1.2	1.8	Ω
Input capacitance	C _{ISS}	V _{GS} =0V ,V _{DS} =30V f=1.0MHZ	-	4000	-	pF
Output capacitance	C _{OSS}		-	680	-	
Reverse transfer capacitance	C _{RSS}		-	23	-	
Turn-on delay time	t _{D(ON)}	V _{GS} =10V, V _{DS} =30V, R _L =1.7Ω, R _G =3Ω	-	11	-	ns
Turn-on Rise time	tr		-	5	-	
Turn-off delay time	t _{D(OFF)}		-	56	-	
Turn-off Fall time	t _f		-	12	-	
Total gate charge	Q _g	V _{GS} =10V, V _{DS} =30V, I _D =20A	-	67	-	nC
Gate-source charge	Q _{gs}		-	12	-	
Gate-drain charge	Q _{gd}		5	8.5	-	

Thermal Characteristics


Parameter		Symbol	Typ	Max	Unit
Maximum Junction-to-Ambient ^A	$\leq 10s$	$R_{\theta JA}$	33	40	$^\circ C/W$
Maximum Junction-to-Ambient ^A	Steady-State		59	75	
Maximum Junction-to-Lead ^B	Steady-State	$R_{\theta JC}$	16	24	

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ C$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10s$ thermal resistance rating.

B: The $R_{\theta JC}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.

Package Information


- SOP-8



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

Recommended Minimum Pads


- SOP-8



Recommended Minimum Pads
Dimensions in Inches/(mm)

Tape and Reel

- SOP-8



Tape Size	Reel Size	M	N	W	W1	H	K	S	G	R	V
12mm	Φ330	Φ330.00 ±0.50	Φ97.00 ±0.30	13.00 ±0.30	17.40 ±1.00	Φ13.00 ±0.5	10.6	2.00 ±0.50	—	—	—

Unit Per Reel:
4000pcs

